



PROLINE PQ IL DVGW

Also available in our Drinking Water product range...



PROLINE PQ AF

Small community, low energy amalgam range with USEPA validation



PROLINE PQ AL

Small to mid-sized community, low energy multi-lamp amalgam range with USEPA validation and built in UVT compensation



PROLINE PQ EO

Energy Optimised medium pressure range, USPA validated with built-in UVT compensation



PROLINE PQ IL

Compact medium pressure range with USEPA validation, for use where space is tight in small to mid-sized communities



www.weuvcare.com

BERSON, HANOVIA & AQUIONICS WORKING TOGETHER AS PART OF THE HALMA GROUP.

Netherlands

t: +31 40 2907777
e: sales@bersonuv.com

China

t: +86 21 61679599
e: china@hanovia.com

USA

t: +1 980 256 5700
e: sales@aquionics.com

Germany

t: +49 611 44575375
e: verkauf@hanovia.com

Malaysia

t: +60 16 440 8834
e: asia@hanovia.com

Canada

t: +1 980.256.5700
e: sales@aquionics.com

United Kingdom

t: +44 1753 515300
e: sales@hanovia.com

Mexico

t: +1 980.256.5700
e: sales@aquionics.com



A Halma company



FM 29365


©2019 Berson Hanovia Aquionics - 910434-3420-01-EN

We UVCare...



PROLINE PQ IL DVGW

Application Optimised UV for Drinking Water





Certified UV treatment for drinking water

Our ProLine PQ IL DVGW systems are aimed specifically at providing third party certified UV disinfection for municipal drinking water. By using a third party certified UV system you can be certain that the UV dose being produced will disinfect the water, eliminate harmful micro-organisms, reduce the bio-burden, protect against bio-fouling and lower operating costs. Each system comes with a certified dry UV sensor allowing checking of UV performance. The UV sensor measures the germicidal output of the UV system and a UV dose read out makes it easy to monitor and log performance. The control system also has the ability to take flow and transmittance meter inputs and calculate the UV dose based on real time operating conditions.



ProLine PQ IL DVGW™ drinking water treatment process



Model Number	Max. power (kW)	No of lamps	Dimensions (mm)				Approx weight (Kg)					
			Chamber		Cab.	Cabinet (fan cooled) ^a	Chamber		Cabinet			
			A	B	C	DN	No***	K*	L	M**	Empty	Fan cooled
ProLine PQ IL DVGW 100	1.8	2	780	310	400	100	1	300	800	1000	42	50
ProLine PQ IL DVGW 200	2.9	1	780	310	400	150	1	300	800	1000	50	55
ProLine PQ IL DVGW 450	5.6	2	780	310	400	200	1	300	1000	1200	78	80
ProLine PQ IL DVGW 1000	11.0	4	780	310	400	200	1	300	1000	1200	78	100
ProLine PQ IL DVGW 4000	17.5	4	896	368	550	350	1	600	1000	2100	150	180
ProLine PQ IL DVGW 5000	34.8	8	896	368	550	350	1	600	1000	2100	150	230
ProLine PQ IL DVGW 15000	52.0	12	1052	446	680	500	1 CC	400	600	2000	240	130
ProLine PQ IL DVGW 29000	52.0	6	1644	728	1200	800	1 CC	400	600	2000	1000	130
							1 PC	1200	600	2100		310

UV CHAMBER	
Material:	StSt 316L / 1.4404
Internal finish:	< 0.8 µm Ra, welds as laid, electropolished and passivated
External finish:	Brushed to K280, electropolished and passivated
Process (mating) connections:	Flange EN 1092-1 PN10
Drain connection:	BSP Socket
End plate:	Removable end plate
Degree of protection:	IP54 equivalent to NEMA 12
Wiper:	Automatic (electrically driven)
Arc tube (lamp):	Medium pressure
Arc tube enclosure:	Doped quartz
Number of arc tubes (lamps):	See table above
Expected lamp life:	9000 hours
Temperature sensor:	Yes
UV sensor:	Dry DVGW compliant UV sensor
Working fluid temperature:	1°C to 60°C
Hydrostatically pressure tested:	Yes
Chamber mounting:	Flow horizontal or vertical (lamps horizontal only)
Operating pressure:	6 bar
Seals:	EPDM, ADI free, EC 1935/2004, FDA 21 CFR 177.2600 approved

CABINET (FAN COOLED)	
Material:	Polyester coated carbon steel, RAL 7035
Degree of protection:	IP54 (NEMA 12)
Supply voltages:	PQ IL DVGW 100-1000: 200-277 V (2ph L1,L2 or 1ph L1+N) PQ IL DVGW 4000-29000: 400-480 V (3ph L1, L2, L3) 50/60 Hz (voltage tolerance ±10% of nominal)
Operating temperature range:	5°C to 35°C
Relative humidity:	<95% non-condensing
Cooling fans:	Yes
Interconnecting cable:	10 m
Variable power:	Stepless variable power (70% reduction from maximum ballast power)

OPTIONS	
Document Support Pack	
Cabinet material:	Stainless steel 304
Operation and Maintenance manual and printed Installation and Commissioning manual in Chinese, English, French, German & Spanish	
Flange options:	PN16, ANSI 150, JIS, Table 'E'
Lead length:	20 and 29 m
In-field UV reference sensor kit	
Control cabinet:	Air conditioning in stainless steel raises control ambient limit to 50°C (in shade) IP rating 65 (NEMA 4X)
Water leak detection:	Detects water leaks from quartz sleeve
Water level sensor:	UV chamber full water detection
Operating pressure:	10 Bar (Not PQ IL DVGW 29000)

HMI / CONTROL	
Display:	4 line LCD, indicating system status including alarms
Operating menu:	3 levels (2 with password protection)
Fault finding:	Event log

CUSTOMER OUTPUTS	
4-20 mA passive output:	UV intensity, ballast power
VFC outputs:	Standby in remote, system standby, system cooling down, any trip, any warning, UV intensity failure, system ready, wiper failure, lamp failure, water leak, water temperature warning, water & cabinet temperature alarm

CUSTOMER INPUTS	
4-20 mA active or passive inputs:	Flow meter
VFC inputs:	Remote stop/start, remote clear message, remote wipe, remote set power high

CUSTOMER COMMUNICATIONS PORT	
Modbus RS 485 serial RTU for SCADA connection	

APPROVALS	
CE marked, UL 508A shop, DVGW certified	

KEY FEATURES	WHAT IT GIVES YOU	BENEFITS FOR YOU
INTELLIGENCE		
Dry DVGW approved UV sensor measuring germicidal wavelengths	Continuous verification of performance and in-built low dose warning	Easy to monitor and log system performance
Flow meter input	UV Intensity monitoring based on actual process conditions when meters are connected	Accurate UV intensity reading guaranteed under wide range of operating conditions
OPTIMISATION		
DVGW certified UV systems	UV system dose equations and sizing have been independently derived	Confidence the system will perform as stated
UV water disinfection	Protects your drinking water from microbiological contamination including chlorine resistant <i>Cryptosporidium</i> and <i>Giardia</i>	Does not affect taste and odour No chemicals
Designed for treatment of drinking water	FDA-approved materials used for all wetted parts	Industry compliant materials
	Flanged connections, high standard internal finish	Designed to international standards
	*Automatic wiper (quartz cleaning)	Self cleaning to maintain performance
INTEGRATION		
Compact design	Can be retrofitted to existing process	Easy integration